

Gazelle S2026i | L2 Manageable Industrial Switch



Product Overview

The Gazelle S2026i is a Layer 2 19" rack-mount manageable industrial switch designed to satisfy broadband backbone transportation in areas of smart grid (IEC 61850-3, IEEE 1613), transportation (EN50121-4), energy and industrial automation. It supports up to 4 GE uplinks, 24 FE downlinks. Network redundancy and reliability are guaranteed with LACP, G.8032 ERPS (<50ms switch-over time), and 24/48 VDC or 110/220 VDC/VAC power supplies.

Highlights

- Compliant with IEC 61850-3 and IEEE 1613 (power substations) as well as EN50121-4 (railway applications)
- Support standardized G.8032 Ethernet ring protection switching with a recovery time less than 50ms
- LACP for optimizing bandwidth utilization
- VLAN and flexible QinQ
- Wide operating temperature range
- IP40 protection level
- Rugged rack-mount design
- MTBF>35 years

Specifications

Interface/Modules:

2*GE SFP ports:

2*GE combo ports

24*FE ports:

SNMP/Console: 1*RJ45

Relay alarm output: 1*1 S.P.D.T.

Dimensions: 440(W)*180 (D) *44(H) mm

Weight: 3Kg

Installation: rack-mount

Operating temperature: - 40 to 85°C

Storage temperature: -40 to 85°C

Humidity: 5% to 95%, non-condensing

Power supply (input Voltage):

- DC 24/48V (18-72V)

- AC/DC 110/220V (AC: 85-264V; DC: 77-370V)

Power consumption: <10W

International Headquarters

Building 2, No. 28 of the Shangdi 6th Street,
Haidian District, Beijing. 100085, China
Tel: +86 10 8288 3305
Fax: +86 10 8288 3056
www.raisecom.com

U.S.A. Headquarters

19337 US 19 North, Suite 306
Clearwater, Florida. 33764. USA.
Tel: +1 888 816 4808
Fax: +1 727 547 9124
Email: sales@raisecomusa.com

Raisecom Technology Co., Ltd.

Copyright©1999-2013
All rights reserved
Technical information is subjected to
change without notice

Access Capacity

- MTU: 16K byte
- Switching buffer size: 12Mbit

Ethernet

- Up to 16k MAC
- Support 4,094 VLANs, flexible QinQ and GVRP
- IEEE 802.3x and back pressure flow controls
- N:1 port-based mirror and flow-based mirror

IP Services

- DHCP server/client/relay/snooping/option82
- IGMP snooping v1/v2/v3, MVR, GMRP, multicast filtering, unknown multicast discard, static multicast group and 1K multicast groups

Traffic Management

- Service classification per port/VLAN/CoS (DSCP)
- Support SP, WRR and SP+WRR scheduling modes, and up to 8 queues per port
- Flow statistics and flow-based mirroring
- Rate limit per port/VLAN/CoS (DSCP)
- Traffic shaping in egress direction

Security

- Secure MAC address
- RADIUS, TACACS+
- IEEE 802.1X based on port/MAC/user
- User management and password protection
- PPPoE Agent, PPPoE+
- dot1x, IP Source Guard, DAI (dynamic ARP inspection)
- Storm control (broadcast, multicast, DLF)

Reliability

- Link aggregation group (LAG) – up to 32 groups with maximum 8 ports in each group, and six load balancing mode based on source/destination IP and/or MAC
- STP/RSTP/MSTP, G.8032 ERPS (recovery time less than 50ms), and IEC62439-6 redundant ring protections
- Port-based Ethernet local loop detection: auto shutdown and recover individual port upon fault

signals

Ethernet OAM

- IEEE 802.3ah EFM-OAM link management
- Dying gasp message in case of power failure

System Management

- Remote management via SNMP v1/v2c/v3, Telnet, CLI and SSH v1/v2
- Local management via console interface
- Raisecom Nview NMS/EMS
- KeepAlive, RMON, LLDP, Syslog
- Relay output alarm, Dry contact alarm, and trap alarm management

Standard Compliance

- IEEE 802.1Q (VLAN), 802.1ad (QinQ), 802.1D (STP), 802.1w (RSTP), 802.1s (MSTP), 802.1p (QoS/CoS Priority), 802.1x (Security), 802.3ad (LAG), 802.3ah (EFM), 802.3x (Flow control), 1588v2 (PTP), 1613(sub-station)
- ITU-T G.8032 (ERPS)
- IEC61000-4-2 (ESD), 61000-4-3 (RS), 61000-4-4 (EFT), 61000-4-5 (Surge), 61000-4-6(RF transmission), 61000-4-8 (Power frequency magnetic fields), 61000-4-9 (Pulsed magnet field), 61000-4-10 (Damped oscillation), 61000-4-12/18 (Shockwave), 61000-4-16 (Common-mode conduction), 61000-6-2 (General industrial standard), 60068-2-6 (Anti-vibration), 60068-2-27 (Shock resistance), 60068-2-32 (Free falling), 61850-3 (transformer substation)
- FCC Part 15/CISPR22 (EN55022): Class A
- In compliance with KEMA, CE and ROHS

International Headquarters

Building 2, No. 28 of the Shangdi 6th Street,
Haidian District, Beijing, 100085, China
Tel: +86 10 8288 3305
Fax: +86 10 8288 3056
www.raisecom.com

U.S.A. Headquarters

19337 US 19 North, Suite 306
Clearwater, Florida, 33764, USA.
Tel: +1 888 816 4808
Fax: +1 727 547 9124
Email: sales@raisecomusa.com

Raisecom Technology Co., Ltd.

Copyright@1999-2013
All rights reserved
Technical information is subjected to
change without notice



Ordering Information

Model	Description
Gazelle S2026i-2GF2GX-24FE-AC	L2 manageable industrial switch with 2*100/1000Base-X SFP ports, 2*GE Combo ports, 24 FE ports, and 110/220V DC/AC power supply
Gazelle S2026i-2GF2GX-24FE-DCW48	L2 manageable industrial switch with 2*100/1000Base-X SFP ports, 2*GE Combo ports, 24 FE ports, and 24/48V DC power supply

International Headquarters

Building 2, No. 28 of the Shangdi 6th Street,
Haidian District, Beijing. 100085, China
Tel: +86 10 8288 3305
Fax: +86 10 8288 3056
www.raisecom.com

U.S.A. Headquarters

19337 US 19 North, Suite 306
Clearwater, Florida. 33764. USA.
Tel: +1 888 816 4808
Fax: +1 727 547 9124
Email: sales@raisecomusa.com

Raisecom Technology Co., Ltd.

Copyright@1999-2013
All rights reserved
Technical information is subjected to
change without notice